



- Backing:** 1.5 mil Aluminum Foil
- Adhesive:** Synthetic Rubber
- Liner:** Polycoated Natural Kraft Paper
- Colors:** Aluminum
- Specifications:** UL 723 Classified
- Standard Sizes:** 48mm x 46M, 72mm x 46M

Applications

- Taping joints and seams in duct work for A/C, heating, and ventilation systems
- General purpose industrial and automotive uses.
- Insulation seaming and patching

Features

- Aluminum Foil Backing
- Synthetic Rubber Adhesive
- UL 723 Classified
- Low VOC Content

Benefits

- Conformable to fit corners and joints
- UV and moisture resistant
- Mold and mildew resistant
- Non-solvent for less odor and low VOC content
- Extreme high tack, aggressive bond to surfaces
- Good all-weather performance
- Meets flammability requirements for use in construction and marine applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.2 mils	0.081 mm	ASTM D-1000
Foil Thickness	1.5 mils	0.038 mm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	0		
Flame Spread	10		
VOC Content	<1 g/L		



Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use and that such use complies with all applicable federal, state and local laws and regulations. This document is not intended to constitute an offer of insurance or any other financial product.



25 Forge Pkwy Franklin, MA 02038
 1-800-343-7875 Fax 1-800-328-4822
 www.berryglobal.com
 12/11/17



hvacaislamientos.com.mx

Calle Excelencia #150 Colonia Villa de San Miguel Guadalupe Nuevo León C.p. 67110
Email: gabriel.perez@hvacaislamientos.com.mx

facebook.com/hvacaislamientos.com.mx